

Izdelek / Product: **JUBIZOL CARBONSTRONG FINISH S 1.5 / 2.0**

IZJAVA O LASTNOSTIH
DECLARATION OF PERFORMANCE
Št. / No. 001/20-CSG

1. **Enotna identifikacijska oznaka tipa proizvoda / Unique identification code of product**
10.02.49

2. **Predvidena uporaba / Intended use**

Zunanji omet na osnovi organskih veziv za dekorativno zaščito fasadnih zidnih površin / External render based on organic binder for decorative protection of facade walls

3. **Proizvajalec / Manufacturer**

JUB d.o.o.
Dol pri Ljubljani 28
SI-1262 Dol pri Ljubljani
Slovenia
www.jub.eu

4. **Sistemi ocenjevanja in preverjanja nespremenljivosti lastnosti / System of AVCP**

Sistem 4 / System 4

5. **Tehnična specifikacija / Technical specification**

EN 15824

6. **Navedene lastnosti / Declared performance**

Bistvene značilnosti / Characteristic	Lastnost / Declaration	Standard / Norm	Tehnična specifikacija / Technical specification
Odziv na ogenj / Reaction to fire	F	EN 13501-1	EN 15824:2017
Sprijemna trdnost / Bond strength	> 0,3 MPa	EN 1542	EN 15824:2017
Toplotna prevodnost $\lambda_{10, \text{suh}}$ / Thermal conductivity $\lambda_{10, \text{dry}}$	0,83 W/mK, P=50%	EN 1745	EN 15824:2017
Paroprepusnost / Water vapour permeability	V2 (srednja) / V2 (medium)	EN ISO 7783-2	EN 15824:2017



Vpijanje vode / Water absorption	W3 (nizko) / W3 (low)	EN 1062-3	EN 15824:2017
Sproščanje nevarnih snovi / Release of dangerous substances	Glej varnostni list / See Safety data sheet		EN 15824:2017

7. **Proizvod je tudi komponenta zunanjega toplotnoizolacijskega sistema z ometom / Product is also component of external thermal insulation composite system with render**

**JUBIZOL EPS, ETA-09/0393
JUBIZOL MW, ETA-10/0334**

**ZAG Ljubljana 1404-CPR-2792
ZAG Ljubljana 1404-CPR-2793**

Lastnosti proizvoda, navedenega zgoraj, so v skladu z navedenimi lastnostmi. Za izdajo te izjave o lastnostih je v skladu z Uredbo (EU) št. 305/2011 odgovoren izključno proizvajalec, naveden zgoraj.

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Podpisal za in v imenu proizvajalca / Signed for and on behalf of the manufacturer by:


Dol pri Ljubljani, 16.10.2020

Danijel Lisičič,
Vodja razvojnega področja



JUB d.o.o.
Dol pri Ljubljani 28
SI-1262 Dol pri Ljubljani
Slovenija



 1404	
20	
JUB d.o.o. Dol pri Ljubljani 28 SI – 1262 Dol pri Ljubljani Slovenia	
Unique identification code of product: 10.02.49 Declaration of performance No.: 001/20-CSG	
EN 15824:2017	
<i>External render based on organic binder for decorative protection of facade walls</i>	
Reaction to fire	F
Bond strength	> 0,3 MPa
Thermal conductivity $\lambda_{10,dry}$	0,83 W/mK, P = 50% (value from EN 1745)
Water vapour permeability	V2
Water absorption	W3
Release of dangerous substances	See Safety data sheet
www.jub.eu	

