

Izdelek / Product: **JUBIZOL BASE FIX**

IZJAVA O LASTNOSTIH
DECLARATION OF PERFORMANCE
Št. / No. 001/19-JBX

1. **Enotna identifikacijska oznaka tipa proizvoda / Unique identification code of product**
 11.01.27

2. **Predvidena uporaba / Intended use**

Maltna zmes za zunaj in znotraj (GP) / Factory-made rendering mortar for internal and external use (GP)

3. **Proizvajalec / Manufacturer**

JUB d.o.o.
 Dol pri Ljubljani 28
 SI-1262 Dol pri Ljubljani
 Slovenia
www.jub.eu

4. **Sistemi ocenjevanja in preverjanja nespremenljivosti lastnosti / System of AVCP**

Sistem 4 / System 4

5. **Tehnična specifikacija / Technical specification**

EN 998-1:2016

6. **Navedene lastnosti / Declared performance**

Bistvene značilnosti / Characteristic	Lastnost / Declaration	Standard / Norm	Tehnična specifikacija / Technical specification
Odziv na ogenj / Reaction to fire	F	EN 13501-1	EN 998-1:2016
Tlačna trdnost / Compressive strength	CS IV	EN 1015-11	EN 998-1:2016
Sprijemna trdnost / Adhesion	> 0,5 MPa – FP: B	EN 1015-12	EN 998-1:2016
Toplotna prevodnost $\lambda_{10, \text{suh}}$ / Thermal conductivity $\lambda_{10, \text{dry}}$	0,83 W/mK, P=50%	EN 1745	EN 998-1:2016



Paroprepusnost (μ) / Water vapour Permeability (μ)	< 20	EN 1015-19	EN 998-1:2016
Vpijanje vode / Water absorption	W2	EN 1015-18	EN 998-1:2016
Trajnost / Durability	NPD		EN 998-1:2016
Nevarne snovi / Dangerous substances	NPD		EN 998-1:2016

7. **Proizvod je tudi komponenta zunanjega toplotnoizolacijskega sistema z ometom / Product is also component of external thermal insulation composite system with render**

JUBIZOL EPS, ETA-09/0393
JUBIZOL S70, ETA-08/0236

ZAG Ljubljana 1404-CPR-2792
ZAG Ljubljana 1404-CPR-3222

Lastnosti proizvoda, navedenega zgoraj, so v skladu z navedenimi lastnostmi. Za izdajo te izjave o lastnostih je v skladu z Uredbo (EU) št. 305/2011 odgovoren izključno proizvajalec, naveden zgoraj.

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Podpisal za in v imenu proizvajalca / Signed for and on behalf of the manufacturer by:

Dol pri Ljubljani, 05.11.2019

Danijel Lisičić,
Vodja razvojnega področja




CE	
19	
JUB d.o.o. Dol pri Ljubljani 28 SI – 1262 Dol pri Ljubljani Slovenia	
Unique identification code of product: 11.01.27 Declaration of performance No.: 001/19-JBX	
EN 998-1:2016	
<i>Factory-made rendering mortar for internal and external use (GP)</i>	
Reaction to fire	F
Compressive strength	CS IV
Adhesion	> 0,5 MPa – FP: B
Thermal conductivity $\lambda_{10, dry}$	0,83 W/mK, P = 50% (value from EN 1745)
Water vapour permeability (μ)	< 20
Water absorption	W2
www.jub.eu	

