

Izdelek / Product: **JUBIZOL UNIWOOL FIX WHITE**

**IZJAVA O LASTNOSTIH**  
**DECLARATION OF PERFORMANCE**  
**Št. / No. 001/22-JUWW**

1. **Enotna identifikacijska oznaka tipa proizvoda / Unique identification code of product**  
11.01.40

2. **Predvidena uporaba / Intended use**

**Maltna zmes za zunaj in znotraj (GP) / Factory-made rendering mortar for internal and external use (GP)**

3. **Proizvajalec / Manufacturer**

JUB d.o.o.  
Dol pri Ljubljani 28  
SI-1262 Dol pri Ljubljani  
Slovenia  
[www.jub.eu](http://www.jub.eu)

4. **Sistemi ocenjevanja in preverjanja nespremenljivosti lastnosti / System of AVCP**

Sistem 4 / System 4

5. **Tehnična specifikacija / Technical specification**

EN 998-1:2016

6. **Navedene lastnosti / Declared performance**

Bistvene značilnosti / Characteristic	Lastnost / Declaration	Standard / Norm	Tehnična specifikacija / Technical specification
Odziv na ogenj / Reaction to fire	F	EN 13501-1	EN 998-1:2016
Tlačna trdnost / Compressive strength	CS IV	EN 1015-11	EN 998-1:2016
Sprijemna trdnost / Adhesion	> 0,5 MPa – FP: B	EN 1015-12	EN 998-1:2016
Toplotna prevodnost $\lambda_{10, \text{suh}}$ / Thermal conductivity $\lambda_{10, \text{dry}}$	0,83 W/mK, P=50%	EN 1745	EN 998-1:2016
Paroprepusnost ( $\mu$ ) / Water	< 20	EN 1015-19	EN 998-1:2016



<i>vapour Permeability (<math>\mu</math>)</i>			
<b>Vpjanje vode / Water absorption</b>	<b>W2</b>	EN 1015-18	EN 998-1:2016
<b>Trajnost / Durability</b>	<b>NPD</b>		EN 998-1:2016
<b>Nevarne snovi / Dangerous substances</b>	<b>NPD</b>		EN 998-1:2016

7. **Proizvod je tudi komponenta zunanjega toplotnoizolacijskega sistema z ometom / Product is also component of external thermal insulation composite system with render**

**JUBIZOL EPS, ETA-09/0393  
JUBIZOL MW, ETA-10/0334**

**ZAG Ljubljana 1404-CPR-2792  
ZAG Ljubljana 1404-CPR-2793**

**Lastnosti proizvoda, navedenega zgoraj, so v skladu z navedenimi lastnostmi. Za izdajo te izjave o lastnostih je v skladu z Uredbo (EU) št. 305/2011 odgovoren izključno proizvajalec, naveden zgoraj.**

*The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.*

**Podpisal za in v imenu proizvajalca / Signed for and on behalf of the manufacturer by:**

Dol pri Ljubljani, 03.10.2022

Danijel Lisičić,  
Vodja razvojnega področja



<b>CE</b>	
22	
JUB d.o.o. Dol pri Ljubljani 28 SI – 1262 Dol pri Ljubljani Slovenia	
Unique identification code of product: 11.01.40 Declaration of performance No.: 001/22-JUWW	
<b>EN 998-1:2016</b>	
<i>Factory-made rendering mortar for internal and external use (GP)</i>	
Reaction to fire	F
Compressive strength	CS IV
Adhesion	> 0,5 MPa – FP: B
Thermal conductivity $\lambda_{10,dry}$	0,83 W/mK, P = 50% (value from EN 1745)
Water vapour permeability ( $\mu$ )	< 20
Water absorption	W2
www.jub.eu	

