



DECLARATION OF PERFORMANCE
According to Annex III of Reg. (EU) n°305/2011

SIGILL Acryl Express 590

DOP-F00040-P-01E

EN 15651-1: **F-EXT-INT**

Acrylic sealant for facades, for interior and exterior application.

Address of manufacturer

N.P.T. S.r.l.
Via G. Rossa, 2 40053 Località Crespellano
VALSAMOGGIA (BO) – ITALY

Evaluation and verification of the construction product performance systems, according to Annex V:

System 3, System 4 for reaction to fire

The notified body **4Ward Testing**, identification number **2538**, performed the determination of the product-type and fire behavior under System 3, in reference to EN 15651, releasing the Report n° **NLR1806**.

The performance of the product identified is in conformity with the declared performance (see below). This declaration of performance is issued under the sole responsibility of the manufacturer.

Valsamoggia, 01/10/2024

Dr. GOLDONI E.
Legal Representative

N.P.T. S.r.l.

Via G. Rossa, 2 - Loc. Crespellano
40053 VALSAMOGGIA (BO) ITALIA
Reg. Impr. BO e C.F. 03467421206
P.IVA IT03467421206 - REA BO-521497



DECLARED PERFORMANCE

EN 15651-1: **F-EXT-INT**

Conditioning: Method A (ISO 8340)

Substrate: Mortar (without primer)

Essential characteristics	performance	Harmonized specification
Reaction to fire (EN 13501)	Classe F	EN 15651-1: 2012
Release of chemical dangerous to the environment and health	See product safety data sheet	
Water tightness and air tightness		
Resistance to flow (ISO 7390)	≤ 3 mm	
Loss of volume (ISO 10563)	≤ 25 %	
Tensile properties - Elongation at break (ISO 8339)	≥ 100 %	
Determination of Adhesion/Cohesion properties at constant temperature (ISO 9046)	pass	
Tensile properties - Elongation at break after immersion in water (ISO 10591)	≥ 100 %	
Durability	No failure	