



DECLARATION OF PERFORMANCE
According to Annex III of Reg. (EU) n°305/2011

SIGILL Acryl Universal 520

DOP-C00150-AK-01E

EN 15651-1: **F-INT**

Acrylic sealant for joints of facade elements, internal applications.

Address of manufacturer

N.P.T. S.r.l.
Via G. Rossa, 2 40053 Località
Crespellano VALSAMOGGIA (BO) –
ITALIA

Evaluation and verification of the construction product performances systems, according to Annex V:

System 3, System 3 for reaction to fire

The notified body **4Ward Testing**, identification number **2538**, performed the determination of the product-type and fire behavior under System 3; System 3 for reaction to fire in reference to EN 15651.

The performance of the product identified is in conformity with the declared performance (see below). This declaration of performance is issued under the sole responsibility of the manufacturer.

Valsamoggia, 01/10/2024

Dr. GOLDONI E.
Legal Representative

N.P.T. S.r.l.

Via G. Rossa, 2 - Loc. Crespellano
40053 VALSAMOGGIA (BO) ITALIA
Reg. Impr. BO e C.F. 03467421206
P.IVA IT03467421206 - REA BO-521497



DECLARED PERFORMANCE

EN 15651-1: **F-INT**

Conditioning: Method A (ISO 8340)
Substrate: Mortar M2 (whitout primer)

Essential characteristics	performance	Harmonized specification
Reaction to fire (EN 13501)	Class E	EN 15651-1: 2017
Release of chemical dangerous to the environment and health	See product safety data sheet	
Water tightness and air tightness		
Resistance to flow (ISO 7390)	≤ 3 mm	
Loss of volume (ISO 10563)	≤ 25 %	
Tensile properties - elongation at break (ISO 8339)	≥ 25 %	
Durability	No failure	