



DECLARATION OF PERFORMANCE
According to Annex III of Reg. (EU) n°305/2011

SIGILL Hybrid Crystal 850

DOP C00310-N-01E

EN 15651-1: **F-INT**

One-component methoxy-silane for facades, internal applications.

Address of manufacturer

N.P.T. S.r.l.
Via G. Rossa, 2 40053 Località Crespellano
VALSAMOGGIA (BO) – ITALIA

Evaluation and verification of the construction product performance systems, according to Annex V:

System 4, System 3 for reaction to fire

The notified body **ISTITUTO GIORDANO**, identification number **0407**, performed the determination of the product-type and fire behavior under System 3, in reference to EN 15651.

The performance of the product identified is in conformity with the declared performance (see below). This declaration of performance is issued under the sole responsibility of the manufacturer.

Valsamoggia, 01/10/2024

Dr. GOLDONI E.
Legal representative

N.P.T. S.r.l.

Via G.Rossa, 2 - Loc. Crespellano
40053 VALSAMOGGIA (BO) ITALIA
Reg. Impr. BO e C.F. 03467421206
P.IVA IT03467421206 - REA BO-521497



DECLARED PERFORMANCE

EN 15651-1: F-INT

Conditioning: Method A (ISO 8340)

Substrate: Mortar M1 (without primer); anodised aluminium (without primer);
glass (without primer)

Caratteristiche fondamentali	prestazione	Norma armonizzata
Reaction to fire (EN 13501)	Class E	EN 15651-1: 2017-03
Release of chemical dangerous to the environment and health	See product safety data sheet	
Water tightness and air tightness		
a) Resistance to flow (ISO 7390)	≤ 5 mm	
b) Loss of volume (ISO 10563)	≤ 45 %	
c) Tensile properties - elongation at break (ISO 8339)	≥ 25 %	