



## DECLARATION OF PERFORMANCE

According to Annex III of Reg. (EU) n°305/2011

### SIGILL Silicone Universal 720

DOP FS0002-W-01E

EN 15651-1: **F-EXT-INT**

Silicone sealant for facades, for interior and exterior application

EN 15651-3: **S**

Silicone sealant for joints in sanitary areas

Address of manufacturer

**N.P.T. S.r.l.**  
**Via G. Rossa, 2 40053 Località Crespellano**  
**VALSAMOGGIA (BO) – ITALIA**

Evaluation and verification of the construction product performance systems, according to Annex V:

System 3, System 3 for reaction to fire

The notified body **SKZ TeConA GmbH**, identification number **01213**, performed the determination of the product-type and fire behavior under System 3, in reference to EN 15651, releasing the following:

Report n° **106139/13-I e 106139/13-III**

The performance of the product identified is in conformity with the declared performance (see below). This declaration of performance is issued under the sole responsibility of the manufacturer.

Valsamoggia, 01/10/2024

*Dr. GOLDONI E.*  
*Legal Representative*

**N.P.T. S.r.l.**

Via G. Rossa, 2 - Loc. Crespellano  
40053 VALSAMOGGIA (BO) ITALIA  
Reg. Impr. BO e C.F. 03467421206  
P.IVA IT03467421206 - REA BO-521497

## DECLARED PERFORMANCE



## EN 15651-1: **F-EXT-INT**

Conditioning: Method A (ISO 8340)

Substrate: Glass (without primer); Aluminum (without primer).

Essential characteristics	performance	Harmonized specification
Reaction to fire (EN 13501)	Class E	<b>EN 15651-1: 2012</b>
Release of chemical dangerous to the environment and health	See product safety data sheet	
Water tightness and air tightness		
Resistance to flow (ISO 7390)	≤ 2 mm	
Loss of volume (ISO 10563)	≤ 30 %	
Tensile properties – tension maintained after immersion in water (ISO 10590)	No failure (60%)	
Tensile properties – maintained tension (ISO 8340)	No failure (60%)	
Durability	No failure	

## EN 15651-3: **S Class S1**

Conditioning: Method A (ISO 8340)

Substrate: Glass (without primer); Aluminum (without primer).

Essential characteristics	performance	Harmonized specification
Reaction to fire (EN 13501)	Class E	<b>EN 15651-3: 2012</b>
Release of chemical dangerous to the environment and health	See product safety data sheet	
Water tightness and air tightness		
Resistance to flow (ISO 7390)	≤ 2 mm	
Loss of volume (ISO 10563)	≤ 30 %	
Tensile behavior – elongation at break after immersion in water (ISO 10591)	≥ 25 %	
Evaluation of the action of microorganisms (ISO 846)	1	
Durability	No failure	