

Page 1/12

Safety data sheet according to UK REACH

Revision: 13.11.2024 Version number 1 Date of the first version: 13.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: SIGILL ACRYL POWER 550

• **Article number:** 5.906.717

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Life cycle stages

PW Widespread use by professional workers

C Consumer use

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU19 Building and construction work

- · Product category PC0 Other
- · Process category

PROC0 Other

PROC11 Spraying

- Environmental release category ERC11a Widespread use of articles with low release (indoor)
- · Application of the substance / the mixture Watertight compound
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

N.P.T S.R.L. via Guido Rossa 2

Dol pri Ljubljani 28 1262 DOL PRI LJUBLJANI

40053 Valsamoggia - Loc. Crespellano (BO) Italia

SLOVENIJA

Tel. +39 051 969109 Fax +39 051 969837 T: + 386 1 5884 183

E: info@jub.si

JUB d.o.o.

infoSDS@nptsrl.com

nosbs@nptsrt.com

 $\cdot \ Further \ information \ obtainable \ from:$

Laura Učakar

T: +386 1 5884 185 F: +386 1 5884 227

E: laura.ucakar@jub.eu

(Contd. on page 2)

Revision: 13.11.2024 Version number 1 Date of the first version: 13.11.2024

Trade name: SIGILL ACRYL POWER 550

(Contd. of page 1)

· 1.4 Emergency telephone number:

UK Emergency number: 999

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment Not applicable.
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Determination of endocrine-disrupting properties Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Revision: 13.11.2024 Version number 1 Date of the first version: 13.11.2024

Trade name: SIGILL ACRYL POWER 550

		Contd. of page
Dangerous compone	nts:	
CAS: 2634-33-5	1,2-benzisothiazol-3(2H)-one	≤0.05%
EINECS: 220-120-9	Eye Dam. 1, H318	
	Aquatic Acute 1, H400	
	Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	
	Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	
	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no.	≤0.0015%
	247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-	
	6] (3:1)	
	Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330	
	Skin Corr. 1C, H314; Eye Dam. 1, H318	
	Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410	
	(M=100)	
	Skin Sens. 1A, H317	
	EUH071	
	Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 %	
	Skin Irrit. 2; H315: 0.06 % ≤ C <	
	0.6 %	
	Eye Dam. 1; H318: C ≥ 0.6 %	
	Eye Irrit. 2; H319: 0.06 % ≤ C <	
	0.6 %	
	Skin Sens. 1A; H317: C ≥ 0.0015 %	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:

If symptoms persist consult doctor.

Rinse out mouth and then drink plenty of water.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB

Revision: 13.11.2024 Version number 1 Date of the first version: 13.11.2024

Trade name: SIGILL ACRYL POWER 550

(Contd. of page 3)

SECTION 5: Firefighting measures

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

 \cdot 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

- · 6.2 Environmental precautions: No special measures required.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

- · Further information about storage conditions: Protect from frost.
- · Storage class: 10

(Contd. on page 5)

Revision: 13.11.2024 Version number 1 Date of the first version: 13.11.2024

Trade name: SIGILL ACRYL POWER 550

(Contd. of page 4)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- \cdot 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

· Hand protection

Protective gloves that meet the criteria of BS EN 374.

Check protective gloves prior to each use for their proper condition.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Eye/face protection

Protective goggles must comply with standard BS EN 166.

Goggles recommended during refilling

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Physical state Fluid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Undetermined.
• Flammability Not determined.

(Contd. on page 6)

Revision: 13.11.2024 Version number 1 Date of the first version: 13.11.2024

Trade name: SIGILL ACRYL POWER 550

(Contd. of page 5) · Lower and upper explosion limit Not determined. · Lower: · Upper: Not determined. · Flash point: >420 °C · Decomposition temperature: Not determined. · pH Not determined. · Viscosity: · Kinematic viscosity Not determined. · Dynamic: Not determined. · Solubility · water: Not determined. · Vapour pressure at 20 °C: 8 hPa · Density and/or relative density · Density at 20 °C: 1.63-1.69 g/cm³ · Relative density Not determined. Not determined. · Vapour density · 9.2 Other information · Appearance: Viscous · Form: · Important information on protection of health and environment, and on safety. · Ignition temperature: Product is not selfigniting. Product does not present an explosion hazard. · Explosive properties: · Solvent content: 5.7 g/l · VOC (EC) 0.34 % · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void Void · Pyrophoric liquids · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void

(Contd. on page 7)

Revision: 13.11.2024 Version number 1 Date of the first version: 13.11.2024

Trade name: SIGILL ACRYL POWER 550

(Contd. of page 6)

Corrosive to metalsDesensitised explosivesVoid

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- \cdot Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:					
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1)					
		- ` /			
Oral	LD50	49.6-75 mg/kg (rat)			
Dermal	LD50	141 mg/kg (rabbit)			
Inhalative	LC50/4 h	0.33 mg/l (rat)			

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 8)

Revision: 13.11.2024 Version number 1 Date of the first version: 13.11.2024

Trade name: SIGILL ACRYL POWER 550

(Contd. of page 7)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Not hazardous for water.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system

Hand over to hazardous waste disposers.

· European waste catalogue				
08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09			
15 01 02	plastic packaging			

(Contd. on page 9)

Revision: 13.11.2024 Version number 1 Date of the first version: 13.11.2024

Trade name: SIGILL ACRYL POWER 550

(Contd. of page 8)

· Recommendation: Dispose of packaging according to regulations on the disposal of packagings.

SECTION 14: Transport informati	on	
· 14.1 UN number or ID number · ADR, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:	Not applicable.	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk accord IMO instruments	ling to Not applicable.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Following regulation was considered in the preparation of document:

Legislation on the occupational health and safety, the chemical legislation and regulations on biocidal products, regulations on classification, packaging and labeling of chemical and biocidal products and requirements on safety data sheets for chemicals and biocidal products composition, as well as regulations on the management of packaging and packaging waste and waste.

· Poisons Act

•	Regul	lated	exp	losives	precursors
---	-------	-------	-----	---------	------------

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

(Contd. on page 10)

Revision: 13.11.2024 Version number 1 Date of the first version: 13.11.2024

Trade name: SIGILL ACRYL POWER 550

(Contd. of page 9)

· Reportable poisons

None of the ingredients is listed.

- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Directive 2004/42/EC
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- \cdot DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

 \cdot Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.

(Contd. on page 11)

Revision: 13.11.2024 Version number 1 Date of the first version: 13.11.2024

Trade name: SIGILL ACRYL POWER 550

(Contd. of page 10)

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

· Recommended restriction of use

Claims contained in this document are based on our actual knowledge at the time of revision of this document. They do not undertake the properties of the product described in terms of the legal provisions for the pledge.

Placing this document as available does not unbind the product customer from its responsibility to comply with all relevant laws and regulations applicable for this product. This is especially valid in the case of product resale or resale of its mixtures or manufactured products from other areas of law and industrial property rights of third parties. If the product described above is changed by crafting or mixing with other materials, it is not possible to transfer claims from this document onto a newly made product, unless otherwise specified. In the case of product re-packaging the customer must attach the required relevant safety information as well.

· Department issuing SDS:

JUB d.o.o.

Product safety department

· Contact:

Laura Učakar

laura.ucakar@jub.eu

· Date of previous version: 13.11.2024

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

(Contd. on page 12)

Revision: 13.11.2024 Version number 1 Date of the first version: 13.11.2024

Trade name: SIGILL ACRYL POWER 550

(Contd. of page 11)

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

· * Data compared to the previous version altered.

a D