

TECHNICAL SHEET 21.03.14-EN



EUROTHERM EPS - T

White EPS T against impact sound

1. Product description

Elastified thermal insulation boards made of expanded polystyrene. For use in floating floors. They permanently retain their properties after loading.

2. Technical data

Board dimension: 1000 x 500 mm
Thickness: 12 mm to 33 mm

3. Resistance

Temperature resistance: 70°C on a long-term basis.

4. Standard

EN 13163:2012+A1:2015

5. Quality

The quality characteristics of the product are determined by European standards. Achieving the declared or prescribed level of quality is ensured by the ISO 9001 quality control system, which includes daily product quality checks in our own laboratories. In manufacturing process, we strictly comply with European standards in the field of energy saving, environmental protection and ensuring safety and health at work, which is confirmed by ISO 50001, ISO 14001 and ISO 45001 certificates.

6. Field of use

In floating floors, to reduce the level of impact sound between floors.

7. Application

Depending on the purpose of use, thermal insulation boards are installed by gluing, mechanical fastening or they

are laid freely.

8. Packaging

Thermal insulation boards are in a package of 0.25 m³, wrapped in an opaque PE-foil. Each package contains a declaration sheet in accordance with the SIST EN 13172 standard.

9. Storage

Store in covered areas, away from sources of heat and flame, do not expose to UV rays, avoid contact with incompatible materials/chemicals.

10. Waste management

The manufacturer guarantees that all its packaging is included in the waste packaging management system (Ur.l.RS, No. 54/21 with all amendments and additions).

11. Technical specifications - 1

CE- technical code EPS-EN 13163-T1-L3-W3-S5-P10-CP2/CP4-SD25/SD15/SD10

Essential characteristic	Mark	Performance	Unit	Declared	Standard
Length	L	1000	mm	L3	EN 822
Width	W	500	mm	W3	EN 822
Thickness	T	12-33	mm	T1	EN 823
Squerness	S	1000/500	mm	S5	EN 824
Flatness	P	1000/500	mm	P10	EN 825
Dimensional stability	DS(N)	NPD	%	NPD	EN 1603
Dim. stability under spec. temp.	DS(70)	NPD	%	NPD	EN 1604
Compressive stress at 10% def.	CS	NPD	kPa	NPD	EN 826
Bending strength	BS	NPD	kPa	NPD	EN 12089
Transverse tensile strength	TR	NPD	kPa	NPD	EN 1607
Compressive creep	CC	NPD	kPa	NPD	EN 1606
Water absorption by total immersion	WL(T)	NPD	%	NPD	EN 12087
Water absorption – LT by diffusion	WD(V)	NPD	%	NPD	EN 12088
Water vapour diffusion resistance	μ	NPD	-	NPD	EN 12086
Thermal conductivity	λD	0,042	W/mK	0,042	EN 12667
Fire resistance (Euroclass)	-	E	-	E	EN 13501-1
Maximum load	-	6500	N/m ²	-	-

12. Technical specifications - 2

Essential characteristic	Mark	Performance		
Nominal thickness (mm)	dl	12	22	33
Thickness under load (mm)	db	10	20	30
Dynamic stiffness	s'	10	25	15
Compressibility	CP	2	4	4
Thermal resistance (m ² K/W)	RD	0,2	0,45	0,7
Thermal transmittance (W/m ² K)	λD/d	4,2	2,1	1,4

13. Certificate

Declaration of properties, in accordance with the European construction products regulation CPR and with the

European standard EN 13163:2012+A1:2015.

Denomination and date of publishing: TRC-085/19-mod, 04.07.2024