

TECHNICAL SHEET 04.01.22-EN



DECOR Primer fine quartz

White primer with fine quartz sand

1. Description, Application

DECOR Primer fine quartz is a white primer intended for achieving more coarse effect on the substrate. It is used for improving the adhesion of decorative finishing materials on low absorbent substrates (such as concrete, cement, gypsum boards, decorative render finishes). If necessary, it can be tinted.

2. Colour Shades

White colour shade. It can be tinted on the JUMIX system

3. Technical data

Packaging	0.7 l	
Density	~1.45 kg/dm ³	
Water dilution mass	21 %	
Water dilution volume	30 %	
Drying time T = +20 °C, relative air humidity = 65 %	Touch dry	~0,5 h
	Completely dry	24 h
Consumption	~125 - 140 ml/m ² (for a one-coat application)	
Recommended number of layers	1	

4. Installation Conditions

The temperature of air and wall surface should not be lower than +5 °C and not higher than +35 °C, and relative air humidity should not exceed 80 %.

5. Surface Preparation

Surface should be solid, dry and clean, without any badly adhered particles, dust, remains of panelling oils, fat linings or other filth.

In normal conditions ($T = +20\text{ }^{\circ}\text{C}$, relative air humidity = 65 %), dry or mature the newly applied renders and levelling compounds for at least a day for each mm of their thickness. Dry concrete surfaces for at least a month. Remove all paint coats that soak easily and quickly in water and coatings of oil paints, varnishes and enamels from the already painted surfaces. Prior to painting, it is obligatory to disinfect surfaces infected with wall mould.

6. Preparation

Prior to use, stir DECOR Primer fine quartz. Then, dilute it with water (maximum 20 % - 40 %) to the consistency corresponding to application technique and method.

7. Application of Primer

The primer is applied by using a roller or brush; An individual wall surface is painted without interruptions from one end to the other. Always treat surfaces inaccessible to a standard paint roller or spraying gun (corners, gutters, narrow reveal surfaces, and similar) first using suitable brushes or smaller paint rollers.

Thoroughly clean the tools with water immediately after use.

8. Storage, Transportation Conditions and Durability

Storage and transportation at temperature $+5\text{ }^{\circ}\text{C}$ to $+25\text{ }^{\circ}\text{C}$, protected from the direct sunlight, out of reach of children, **MUST NOT FREEZE!!**

Durability when stored in originally sealed and undamaged packaging: at least 36 months.

9. Other Information

Technical instructions contained in this brochure are provided based on our experience and are given as a guideline to achieve the optimum results. We shall not accept any responsibility for damage caused by incorrect selection of a product, incorrect use or unprofessional work.

Tinted product may differ from the sample in the colour chart or from the approved sample. However, the total colour difference ΔE_{2000} – it is determined in accordance with the ISO 7724/1-3 and with a mathematical model CIE DE2000 – does not exceed 1.5. In order to check the colour shade, a dry application of paint on a test surface is compared to a standard of the concerned shade. A colour shade of a paint made on the basis of other colour charts is the best possible approximation for JUB's product bases and tinting agents. Therefore, in such cases the total colour difference from the desired shade may be even higher than the value guaranteed above. A difference in colour shade, which is the result of unsuitable working conditions, of a product preparation technique, which differs from the one in this technical sheet, of failure to follow the equalisation rules, of the application of the product onto an unsuitably prepared, over or not enough absorbing surface, more or less coarse surface, or on a wet or not dried enough surface cannot be subject of complaint.

Safety measures: Follow the instructions on the safety data sheet of the product.

This technical sheet supplements and replaces all preceding editions. JUB reserves the right to change and supplement data in the future.

Denomination and date of publishing: R-SRB /ver.1, 18.07.2024