

## TECHNICAL SHEET 01.04.03-EN



# JUBOCIDE Plus

## Agent for preventing wall mould

### 1. Description, Application

JUBOCIDE Plus is an aqueous suspension of biocidal substances, which, as an additive to interior wall dispersion paints, effectively prevents or inhibits the growth and development of most of the most widespread wall molds. The product is only useful as a preventive fungicidal additive to wall paints and does not act as a disinfectant for infected wall surfaces.

Classification according to ZBioP: protective agent for coatings, protective agent in the construction industry.

List of colors for which the biocidal preparation can be used: JUPOL Classic, JUPOL Silver, JUPOL Strong protect, JUPOL Thermo, JUPOL Junior, JUPOL Trend, JUPOL Special, JUPOL Brilliant, JUPOL Latex matt, JUPOL Latex semi matt and JUPOL Latex satin.

### 2. Colour Shades

- milky thin liquid

### 3. Technical data

Packaging	0.5 l
Density	1 kg/dm <sup>3</sup>
Water dilution	0 %
Drying time T = +20 °C, relative air humidity = 65 %	drying time of the selected color
Consumption	20-100 ml/m <sup>2</sup>
Recommended number of layers	1-2

## 4. Installation Conditions

Temperature of the air and the surface should not be lower than +5 °C and not higher than +35 °C and relative air humidity should not exceed 80 %.

## 5. Instruction for Use

Before use, shake the bottle well and mix it well into the paint; dosage: 20 to 100 ml per liter of interior wall paint. The added preparation can change the consistency of the paint, so when diluting with water, consider the amount of added preparation already as part of the dilution. The added preparation does not affect the shade of the paint and other technological properties important for the application of the paint. The dried paint coating does not pose a threat to human and animal health. Before the first application of paint, already infected surfaces should be washed with a wet cloth and disinfected dry with ALGICIDE Plus concentrate or ALGICIDE Plus spray. Wash the tool thoroughly with water immediately after use.

## 6. Medical integrity

The dried application of paint protected by the preparation JUBOCIDE Plus is not harmful to health.

## 7. Storage, Transportation Conditions and Durability

Storage and transportation in a closed packaging at temperature +5°C to +25°C, protected from the direct sunlight, out of reach of children. **MUST NOT FREEZE.**

Durability when stored in originally sealed and undamaged packaging: at least 24 months.

## 8. Other Information

Technical instructions are given based on our experiences and are given as a guideline for achieving optimal results. We cannot take any responsibility for the damage, caused by incorrect selection of a product, incorrect use or unprofessional work. JUB also bears no responsibility in cases where the substrate for the application of our products is prepared inadequately or with materials of inadequate quality from other manufacturers. In the case of applying our products to existing substrates of old coatings or pre-prepared substrates with materials from other manufacturers, it is obligatory to make appropriate test fields with all the intended applications of JUB products, in accordance with the technical instructions, before starting the work.

Safety measures: Follow the instructions on the safety data sheet of the product.

This technical sheet supplements and replaces all preceding editions. We reserve the right to change and supplement data in the future.

Denomination and date of publishing: TRC- 068/21-čad, 04.11.2024